

## 802.11n USB Module

### WUBR-216GN

#### 802.11 b/g/n USB Module



- Up to 300Mbps
- Realtek RTL8192CU-GR
- Antenna: 2 U.FL connectors, 2T2R
- Host interface: USB 2.0 type A or 4-pin
- Output power: up to 16dBm
- Supports: Windows XP/Viats/Win 7, Linux, MAC

## 802.11n Mini PCI Express Module

### WPEA-127NI

#### 802.11a/b/g/n Mini Card



- Up to 450Mbps
- Atheros AR9390
- Antenna: 3 U.FL connectors, 3T3R
- Host Interface: Mini Card
- Output Power: Up to 19dBm
- Wide temperature range: -40~80°C
- Supports: Windows XP/Vista/Win 7, Linux

### WPEA-127N

#### 802.11a/b/g/n Mini Card



- Up to 450Mbps
- Atheros AR9380
- Antenna: 3 U.FL connectors, 3T3R
- Host Interface: Mini Card
- Output Power: Up to 18dBm
- Supports: Windows XP/Vista/Win 7, Linux

### WPEA-121N

#### 802.11a/b/g/n Half Mini Card



- Up to 300Mbps data rate
- Atheros AR9382
- Antenna: 2 U.FL connectors, 2T2R
- Host Interface: Half Mini Card
- Output Power: Up to 17dBm
- Supports: Windows 2000/XP/Vista/Win7, Linux

### WPER-118GN

#### 802.11b/g/n Half Mini Card




- Up to 150Mbps data rate
- Ralink RT5390
- Antenna: 1 U.FL connector, 1T1R
- Host Interface: Half Mini Card
- Output Power: Up to 19dBm
- Supports: Windows 2000/XP/Vista/Win7, Linux

## AP Board

### WAPA-205N(P)

#### AP Development Solution



- Atheros AR7161 (CPU), and AR9220, AR9223
- Interface: 1 Gigabit Ethernet, 1 DC power jack, 1 USB port
- 64MB RAM, 16MB Flash
- 802.3af PoE (optional)
- Multi-applications: AP, Bridge, WDS
- SDK provided

## 802.11n Dual-Band Gigabit



### **WAPA-205N**

#### **802.11an+gn Concurrent Gigabit Indoor AP**

- Interface: 1 Gigabit LAN, 1 USB port
- 802.3af PoE
- Security: 64/128-bits WEP, WPA, WPA2, 802.1x, Layer2Isolation, ACL
- Multi-modes: AP, Bridge, WDS
- Supports WMM, DHCP client/server, NTP, Static routing, Port forwarding, Multi-SSID

## SOHO IP Camera Series



### **CAS-675/P/W**

#### **Wired/Wireless(11n)Megapixel ICR Pan/Tilt**

- 2 Mega Pixel CMOS sensor
- Concurrent H.264,MPEG4,MJPEG
- Built-in ICR
- Easy WiFi set up by pushing WPS button
- 2-way audio support
- 32 channels IPCam Center
- IE7or above, Firefox 3.5or above and Safari
- 802.3af PoE built in (CAS-675P)

NEW Products

**SparkLAN III**  
Connections Made Easy